

FULL CONTROL 680 W DRIVER DRIVEN



FULL SPECTRUM LIGHT WITH MORE EVEN SPREAD.

RRP:

CONTROLLABLE.

DIMMABLE.

LINKABLE.

CONTROLS ANY LED FIXTURE ACCEPTING 0-10V SIGNAL.

SETS PHOTOPERIOD, DIMMING, SUNRISE AND SUNSET RAMPING.

SIMPLE 5-BUTTON CONTROLS.


MAINS ADAPTOR PLUG SUPPLIED.



BIG ON QUALITY, SMALL ON PRICE.

TECHNICAL SPECIFICATIONS

Full Spectrum
1870 µmol/s
2.75 µmol/J
680 W
200 – 264 V, 50/60 Hz
36 – 56 V DE
6.7 - 15.0 A
L90: >50,000 hr
IP65
7.8 kg
108 x 108 x 10 cm





SUNRISE SUNSET

COMPATIBLE



EVEN MORE CROP GROWTH



0-100% DIMMING QUICKMOUNT DRIVER





BLUETOOTH MESH COMPATIBLE

GROW-LUMII.COM Search LUMii Lighting





PPF (µmol/s) is the measure of how much plant usable light is being produced by a fixture PPE (µmol/J) is the measure of how efficient a fixture is at turning energy into light

If you want to grow bigger plants, PPF is more important than PPE, as it directly tells you the total light output of a fixture. The higher the better!